

## ABSTRACT OF THE DISCLOSURE

It is an object of the present invention to provide a method for recording data in an optical recording medium which can record data in a write-once type optical recording medium at a high linear recording velocity using a laser beam having a low recording power.

The method for recording data in an optical recording medium according to the present invention is constituted so that when data are to be recorded in an optical recording medium including a substrate, a first recording layer and a second recording layer by projecting a laser beam whose power is modulated in accordance with a pulse train pattern including pulses whose levels are set to levels corresponding to a recording power  $P_w$  and a bottom power  $P_b$  onto the optical recording medium and forming a recording mark at a predetermined region of the first recording layer and the second recording layer, as a linear recording velocity increases, the power of the laser beam is modulated using a pulse train pattern including a smaller number of pulses whose level is set to a level to the recording power  $P_w$ , thereby forming a recording mark.

According to the present invention, since the power of a laser beam is modulated using a pulse train pattern including a smaller number of pulses whose level is set to a level to the recording power  $P_w$  as a linear recording velocity increases, it is possible to record data in an optical recording medium using a laser beam having a low recording power even when a linear recording velocity is high and on the other hand, it is possible to prevent cross-talk of data from increasing even when a linear recording velocity is low. Therefore, it is possible to employ a semiconductor laser having a relatively low output even when data are recorded at a high linear recording velocity.

(12)特許協力条約に基づいて公開された国際出願

(19) 世界知的所有権機関  
国際事務局(43) 国際公開日  
2003年12月11日 (11.12.2003)

PCT

(10) 国際公開番号  
WO 03/102931 A1

(51) 国際特許分類: G11B 7/0045, 7/24

(21) 国際出願番号: PCT/JP03/06922

(22) 国際出願日: 2003年6月2日 (02.06.2003)

(25) 国際出願の言語: 日本語

(26) 国際公開の言語: 日本語

(30) 優先権データ:  
特願2002-159998 2002年5月31日 (31.05.2002) JP(71) 出願人 (米国を除く全ての指定国について): ティー  
ディーケー株式会社 (TDK CORPORATION) [JP/JP];  
〒103-8272 東京都中央区日本橋一丁目13番1号  
Tokyo (JP).

(72) 発明者; および

(75) 発明者/出願人 (米国についてのみ): 加藤 達也  
00 (KATO, Tatsuya) [JP/JP]; 〒103-8272 東京都中央区  
1-日本橋一丁目13番1号 ティーディーケー株式会  
社内 Tokyo (JP). 平田 秀樹 (HIRATA, Hideki) [JP/JP];  
〒103-8272 東京都中央区日本橋一丁目13番1号  
ティーディーケー株式会社内 Tokyo (JP). JPX(74) 代理人: 大石 皓一, 外(OISHI, Koichi et al.); 〒101-  
0063 東京都千代田区神田淡路町一丁目4番1号 友  
泉淡路町ビル8階 Tokyo (JP).(81) 指定国 (国内): AE, AG, AL, AM, AT, AU, AZ, BA, BB,  
BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK,  
DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU,  
ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT,  
LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ,  
OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ,  
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,  
ZM, ZW.(84) 指定国 (広域): ARIPO 特許 (GH, GM, KE, LS, MW, MZ,  
SD, SL, SZ, TZ, UG, ZM, ZW), ユーラシア特許 (AM,  
[続葉有])(54) Title: METHOD FOR RECORDING DATA TO OPTICAL RECORDING MEDIUM, DEVICE FOR RECORDING DATA  
TO OPTICAL RECORDING MEDIUM, AND OPTICAL RECORDING MEDIUM

(54) 発明の名称: 光記録媒体へのデータの記録方法、光記録媒体へのデータの記録装置および光記録媒体

E  
パルス数

		2T	3T	4T	5T	6T	7T	8T
A ↓ D 記録線速度	低(VL)	1	2	3	4	5	6	7
	B	1	1	2	2-3	2-4	2-5	2-6
		1	1	1	2	2-3	2-4	2-5
	中(VM)	1	1	1	1	2	2-3	2-4
	C	1	1	1	1	1	2	2-3
		1	1	1	1	1	1	2
	D							
	高(VH)	1	1	1	1	1	1	1

A...RECORDING LINEAR VELOCITY  
B...LOW (VL)  
C...MIDDLE (VM)D...HIGH (VH)  
E...NUMBER OF PULSES

(57) Abstract: A method for recording data to an optical recording medium capable of recording data onto a write once optical recording medium with a high recording linear velocity by using a laser beam of a low recording power. As the data recording linear velocity increases, a pulse string pattern having a smaller number of pulses of recording power is used to modulate the laser beam power. Even when the data recording linear speed is high, it is possible to record data by using a laser beam of a low recording power. On the other hand, when the recording linear velocity is low, it is possible to suppress cross talk. Even when the data recording linear velocity is high, it is possible to use a semiconductor laser of comparatively low output.

[続葉有]

WO 03/102931 A1